

REMARKS

Enclosed herewith is a Substitute Specification in which the specification as filed has been amended in various places to correct typographical and grammatical errors, and also to add section headings.

In support of the above, enclosed herewith is a copy of the specification as filed marked up with the above changes.

The undersigned attorney asserts that no new matter has been incorporated into the Substitute Specification.

The claims have been amended to more clearly define the invention as disclosed in the written description. In particular, claim 6 has been cancelled, while claim 7 has been made a proper independent claim. In addition, the claims have been amended for clarity.

Applicants believe that the above changes answer the Examiner's 35 U.S.C. 112, paragraph 1, rejection of claim 3, and respectfully requests withdrawal thereof.

The Examiner has rejected claims 1-4 and 7 under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent 6,160,491 to Kitao et al. in view of U.S. Patent 6,309,275 to Fong et al. The Examiner has further rejected claim 5 under 35 U.S.C. 103(a) as being unpatentable over Kitao et al. in view of Fong et al., and further in view of U.S. Patent 6,130,625 to Harvey. In addition, the Examiner has rejected claim 6 under 35 U.S.C. 103(a) as being

unpatentable over Kitao et al. in view of Fong et al., and further in view of U.S. Patent 6,574,798 to Bradley et al. Finally, the Examiner has rejected claim 8 under 35 U.S.C. 103(a) as being unpatentable over Kitao et al. in view of Fong et al., and further in view of U.S. Patent 6,133,847 to Yang.

The Kitao et al. patent discloses a remote controller, remote control interface, and remote control system including a remote controller and a remote control interface, in which a remote controller includes a memory containing control code tables corresponding to the devices to be controlled. The remote controller sends a trigger signal to the remote control interface which, in response, sends a device code back to the remote controller identifying the device to which the remote control interface is connected, thereby identifying which of the control code tables contained in the memory is to be used by the remote controller for controlling the selected device. In a further embodiment, upon receipt of the trigger signal, the remote control interface sends a complete code table for the connected device back to the remote controller.

The Fong et al. patent discloses interactive talking dolls which, in response to an activation signal, one doll performs a function and then causes the other doll to perform a complementary function. Fong et al. further discloses "Switch connections 32 may be coupled to a switch 30 located on or near the toy (such as in

body 18 of doll 12, 14) or a key 114 of a keyboard coupled to circuit 100. Infrared detector/receiver 34 receives a signal either from an infrared emitting diode, similar to IR emitting driver 42 of circuit 100, of a circuit (substantially identical to circuit 100) in an associated toy or from a remote control device (such as a household television remote controller) which can generate infrared signals. Use of a remote control device for activating the toy of the present invention will be described in greater detail below." (col. 7, line 63 to col. 8, line 6). Fong et al. then describes how the dolls are programmed using the remote control (col. 14, lines 3-43).

The subject invention concerns a remote control device which is capable of controlling at least one further electronic device. To that end, the remote control device includes a memory for storing a set of code data corresponding to the functions to be controlled of the at least one further electronic device. This memory is connected to a control signal generator for generating control signals corresponding to the code data for transmittal to the at least one further electronic device, which includes a control signal input for receiving the control signals.

However, in addition to the control signal generator for generating and transmitting control signals corresponding to the stored code data, the remote control device of the subject invention further includes a code data output unit connected to the

memory for selectively reading and transmitting all or a subset of the code data stored in the memory to a first electronic device of the at least one further electronic device, the first electronic device having a data input for receiving the transmitted code data, and a memory for storing the received code data. As described in the Substitute Specification on page 2, line 20 to page 3, line 17 (paragraph [0005]), by enabling the remote control device to download its stored code data to the memory of a first electronic device, in the event that the code data stored in the memory of the remote control device is lost (for example, due to battery failure), the code data may subsequently be retrieved from the memory of the first electronic device, and as such, re-stored in the memory of the remote control device.

Applicants submit while both Kitao et al. and Fong et al. disclose generating and transmitting control signals from a remote control device to a controlled device for controlling operating functions of the controlled device, neither Kitao et al. nor Fong et al. show or suggest transmitting all (or a subset) of the code ⁽¹⁾ data, used to form the control signals, from the remote control device to a first electronic device for storage in a memory of the first electronic device.

The Harvey patent discloses a universal remote control with incoming signal identification, in which a universal remote control "learns" the signals of a "native" remote control by


analyzing the signal being transmitted by the native remote control in order to identify the Protocol being used by the native remote control in forming its output signals. However, Applicants submit that the Harvey patent neither shows nor suggests an identifier signal which identifies the transmission protocol. Further, Applicants submit that Harvey does not supply that which is missing from Kitao et al. and Fong et al., i.e., transmitting all (or a subset) of the code data, used to form the control signals, from the remote control device to a first electronic device for storage in a memory of the first electronic device. Moreover, Harvey neither shows nor suggests transmitting an identifier signal with code data (which Harvey does not transmit) to a first electronic device for storage.

While the rejection based on Bradley et al. is moot (due to the cancellation of claim 6), Applicants would like to point out that the television appliance 14 and the TV 12, while being in the same classification (e.g., set-top box and television set), are not the one and the same device, but rather are two separate, though related, devices. Further, Applicants submit that Bradley et al. does not supply that which is missing from Kitao et al. and Fong et al., i.e., transmitting all (or a subset) of the code data, used to form the control signals, from the remote control device to a first electronic device for storage in a memory of the first electronic device.

The Yang patent discloses a configurable remote control device which is capable of downloading program control data. However, Applicants submit that Yang does not supply that which is missing from Kitao et al. and Fong et al., i.e., transmitting all (or a subset) of the code data, used to form the control signals, from the remote control device to a first electronic device for storage in a memory of the first electronic device.

Applicant believes that this application, containing claims *, is now in condition for allowance and such action is respectfully requested.

Respectfully submitted,

by 
Edward W. Goodman, Reg. 28,613
Attorney
Tel.: 914-333-9611

CERTIFICATE OF MAILING

It is hereby certified that this correspondence is being deposited with the United States Postal Service as First-class mail in an envelope addressed to:

COMMISSIONER OF PATENTS AND TRADEMARKS
P.O. BOX 1450
ALEXANDRIA, VA 22313-1450

On February 12, 2004
By Burnett James

ARRANGEMENT INCLUDING A REMOTE CONTROL DEVICE
AND A FIRST ELECTRONIC DEVICE



BACKGROUND OF THE INVENTION

Field Of The Invention

[0001] The invention relates to an arrangement including a remote control device and at least a first electronic device, said remote control device having a first memory for storing a set of code data for controlling a further electronic device, ~~which the first memory is being~~ connected to an input of a signal generator ~~to for supplying~~ said code data to said input, ~~which the signal generator is being~~ adapted to generate, on the basis of said code data, control signals for controlling said further electronic device, and to transmit said control signals to said further electronic device, said first electronic device having a data input arranged to receive data from said remote control device.

Description Of The Related Art

[0002] Such arrangements are generally known from audio and video apparatuses. In the known arrangements, the remote control device has a first memory which is loaded with code data retrieved from, for example, a smart card. Once the code data has been retrieved from the smart card and loaded into the first memory, the smart card may be disposed of. To control the further electronic device, the user presses or touches a key of the remote control

device, which causes the code data assigned to the selected key to be retrieved from the first memory. The retrieved code data is supplied to the signal generator, which generates a control signal based on the retrieved code data. The generated signal is then
5 transmitted to the electronic device to control the latter.

[0003] A drawback of the known arrangement is that the generation of a backup of the code data is rather laborious. A user who wishes to generate a backup version of the code data is obliged to retrieve them one by one from the first memory by each time,
10 pressing or touching the assigned key. Such an operation is time-consuming and there is a fair chance that the user will omit to press certain keys, which results in an incomplete backup. Moreover, it is the control signal and not the code data as such that is transmitted.

15

SUMMARY OF THE INVENTION

[0004] It is an object of the present invention to provide a more user-friendly way of generating a backup version of the code data.

20 [0005] An arrangement according to the invention is characterized in that said remote control device has a code data output unit connected to said first memory, said code data output unit having a further input for receiving an upload signal and being adapted to read, under control of said upload signal, at
25 least a subset of said set of code data from said memory, said code

data output unit being further adapted to transmit said subset burst-wise to said data input of said first electronic device, ~~which said first electronic device includes including~~ a second memory for storing a received subset. By including a code data output unit in the remote control device and a second memory in the first electronic device, the code data as such can be retrieved from the first memory and transmitted to the second memory as code data in order to be stored in this second memory. In this way, at least a second subset of the code data is available not only in the first memory but also in the second memory, which belongs to the first electronic device. Thus, ~~so~~ when the code data in the remote control device is lost, for example, due to a battery failure, the code data can be downloaded from the second memory and there is no need to buy a new smart card. Moreover, by sending the code data subset burst-wise to the first electronic device, it is no longer necessary to send and retrieve them by pressing one key after the other on the remote control device.

[0006] A first preferred embodiment of an arrangement according to the invention is characterized in that said signal generator is connected to said code data output unit, ~~which is said code data output unit being~~ adapted to generate a control signal after reading of said subset and to transmit said control signal and said subset to said signal generator, said signal generator being adapted to generate a code data signal, which includes said subset, upon receipt of said control signal and to transmit said code data

signal to said data input of the first electronic device, ~~which~~
said first electronic device includes including a signal decoder
adapted to retrieve said subset from a received code data signal.

In this way, the transmission of the subset to the second memory is
5 effected by means of the signal generator without the transmission
of the control signals or the operation of the further electronic
device being affected.

[0007] A second preferred embodiment of an arrangement according
to the invention is characterized in that said first electronic
10 device includes a verification unit connected to said data input,
said verification unit being adapted to compare a received subset
with subsets stored in said second memory and to generate a first
flag if said received subset is not stored in said second memory.
The presence of a verification unit makes it possible to verify
15 whether the newly supplied subset has already been received by the
first electronic device.

[0008] A third preferred embodiment of an arrangement according
to the invention is characterized in that said verification unit is
adapted to generate a second flag if said received subset is
20 already stored in said second memory, said verification unit being
further adapted to inhibit, under control of said second flag, the
storage of said received subset in said second memory. Thus, it is
achieved that only subsets which are not yet stored in the second
memory will be stored.

[0009] Preferably, said signal generator is adapted to generate said control signal in accordance with a predetermined transmission protocol, said code data output unit being adapted to include an identifier, which identifies said transmission protocol, into said subset. When a universal remote control device is used, the identifier makes it possible to add the protocol to the code data and to furnish the protocol upon loading of a subset retrieved from the second memory.

[0010] The invention also relates to a remote control device forming part of said arrangement.

[0011] Preferably, said remote control device is a user-configurable remote control device. Since user-configurable remote control devices have volatile memories, the present invention offers a suitable solution to load or update them directly from the first electronic device without use of a smart card.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The invention will now be described in more detail with reference to the drawings, which show a preferred embodiment of a communication system according to the invention. In the drawings—:

[0013] Figures 1 and 2 illustrate, schematically, an arrangement according to the invention;

[0014] Figures 3 and 4 illustrate, schematically, an electronic circuit of the remote control device and of the first electronic device, respectively;

[0015] Figure 5 shows a flow-chart illustrating the operation of the remote control device when code data is to be transmitted; and

[0016] Figure 6 shows a flow-chart illustrating the operation of the first electronic device upon receipt of a code data signal.

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] In the drawings, the same or similar elements bear the same reference signs. The arrangement illustrated in Figure 1 comprises a remote control device 1 and at least one further
10 electronic device 2, 3, 4 and 5. The number of electronic devices shown in Figure 1 is of course arbitrary and the arrangement may include more or less devices than the four illustrated. The devices are formed by, for example, a television receiver 2, a video recorder 3, an audio amplifier 4, and a set-top box 5. In the
15 following description, the first electronic device ~~5 being~~ is, for example, ~~a the~~ the set-top box 5. The remote control is adapted to send control signals to the electronic devices 2, 3 and 4, and to communicate with the first electronic device 5.

[0018] The remote control device 1 has several command keys 8, 9
20 and 10, which are either formed by resilient push buttons or by soft keys, displayed on a display screen. Activation of one of the keys initiates the generation of a control signal, which is transmitted to the relevant device in order to control this device.

[0019] The remote control device 1 may be a user-configurable
25 remote control device which can be loaded either by a smart card or

by other means, such as direct connection to a database. However, it will be evident that the present invention is not limited to a user-configurable remote control device.

[0020] As illustrated in Figure 2, the first electronic device 5 has a data input 20 ~~arranged to receive~~for receiving data from the remote control device 1. The further device 3 has a control signal input 23 for receiving control signals from the remote control device 1. For this purpose, the remote control device 1 includes a transmitter 15. The remote control device further includes a code data output unit 21 and a first memory 13 connected to a data processing unit 12.

[0021] Figure 3 is a block diagram which schematically shows the electronic circuit of the remote control device 1. The ~~latter~~ ~~has~~remote control device 1 includes a communication bus 11, to which the data processing unit 12, for example, a microprocessor, is connected. The first memory 13 and a key module 16, as well as an interface 14, are also connected to the bus 11. The key module 16 forms the interface between the command keys 8, 9 and 10 and the processing unit 12 and converts the actuation of a key into an instruction to be processed by the data processing unit 12. The first memory 13 serves for storing a set of code data for controlling at least one further electronic device (2, 3, 4). The interface 14 is further connected to a second communication unit 15, preferably an infrared transmitter, for transmitting signals to the electronic devices, and to the code data output unit 21.

[0022] Upon activation of one of the keys by a user, for example, a key 8-1 "Volume up", the key module 16 transmits an instruction identifying the activated key to the data processing unit 12. On the basis of this instruction, the data processing unit 12 generates an address ~~in order to address~~for the first memory 13 and reads out the code data assigned to the activated key. The code data thus read is then transferred to the interface 14, which includes a signal generator ~~adapted to generate~~for generating, on the basis of the supplied code data, a control signal for
10 controlling one of the further electronic devices. The control signal is sent to the further electronic device by means of the transmitter 15.

[0023] Each of the further electronic devices is adapted to detect a control signal emitted by the remote control device. The
15 control signal is, therefore, usually modulated on a carrier wave in accordance with a predetermined transmission protocol, to which the electronic device is responsive. The signal generator of the interface 14 modulates the code data on the carrier wave depending on the electronic device for which the signal is intended. The
20 signal is also modulated in accordance with the protocol of the addressed electronic device. If the remote control device 1 is a user-configurable universal remote control device, it is necessary to supply the necessary data, including the transmission protocol and the carrier wave frequency to the signal generator, in order to
25 generate a control signal that can be received and decoded by the

addressed electronic device. Therefore, it is important to store not only the code data assigned to each of the keys, for example, to increase the sound volume of the television receiver, but also the carrier frequency and the modulation protocol. Instead of by means of a carrier frequency, the control signal could be formed by means of a series of pulses, wherein either the number or the length of the pulses determines the contents of the control signal.

[0024] Figure 4 is a block diagram which schematically shows the electronic circuit of the first electronic device 5. The first electronic device has a communication bus 17, to which a data processing unit 24 and a second memory 18 are connected. An interface 19 is also connected to bus 17. The data input 20 is connected to the interface 19. This data input 20 serves to receive code data from the remote control device 1. It should be noted that the first electronic device may also be formed by a conventional PC in connection with the Internet or by a television or audio receiver connected to a Cable Antenna TV system (CATV). In the latter cases, the second memory 18 is formed by the RAM of the PC or by a buffer capable of storing, at least temporarily, data downloaded from the Internet or from the CATV supplier. It is not necessary that the data input 20 and the second memory are physically connected to the same bus 17. They could be remote from each other. However, it is important that they can communicate with each other.

[0025] The second memory 18 of the first electronic device 5 serves for storing code data originating from the first memory 13 of the remote control device 1. In order to transfer the code data assigned to each of the command keys, the remote control device 1 5 should be switched to an upload mode. For this purpose, the user presses, for example, a key 22 on the remote control device 1. Alternatively, the user may press another key, for example, the volume up key, twice or three times or press two keys successively depending on how the remote control device is constructed. By 10 pressing (KY) the appropriate key or keys, an upload signal is generated (ULS) as illustrated schematically in the flow-chart shown in Figure 5. The different instructions illustrated in this flow-chart are executed under control of the data processing unit 12.

15 [0026] The upload signal is supplied to the code data output unit 21 in order to activate the latter, and the data processing unit 12 requests (AC) the user if all the code data should be read from the first memory. This is realized, for example, by displaying a message on a display of the remote control device 1, or by making 20 keys light up. When the user indicates that not all the code data but only a subset of the code data set (AC:N) should be selected, the data processing unit 12 requests the user (IND G) to indicate which ~~second~~ subset should be selected. Thus the user may request, for example, that only the code data for controlling the VCR be 25 selected. The user then indicates (GSA) which subset should be

selected, for example, by pressing the key associated with the selected device.

[0027] Once the user has indicated which code data should be selected, the code data output unit receives the user's

5 instructions, i.e., either all code data or only a selected subset, and starts to generate (GA) the addresses of the first memory locations where the selected code data are stored. The generated addresses are then supplied to the first memory in order to read and retrieve (RDA) the code data stored at the addressed memory
10 locations.

[0028] Depending on the configuration of remote control device and the first electronic device, the read code data is then configured into a transmittable message (CTM). For example, in the case that the remote control device and the first electronic device

15 can be connected by means of a wire, the code data is digitally transferred in a manner similar to that in which data is transmitted in a computer network. If, on the other hand, the code data is transmitted by means of an infra-red or ultrasonic signal, the code data is modulated as a series of pulses. However, these
20 pulses differ from those used to transfer a control signal, in order to not disturb the operation of the other electronic devices. The signal generator could be used for transmitting the code data. However, the signal generator is then switched to a mode suitable to transmit such code, for example, by means of a control signal
25 generated by the code data output unit.

[0029] If the signal generator is adapted to generate control signals in accordance with a predetermined transmission protocol, for example, RC 5 for Philips devices, this protocol may also be included in the data transmitted to the first electronic device. In 5 the latter case, the code data output unit ~~is adapted to generate~~generates an identifier, which identifies this protocol, and ~~to include~~includes (INI) this identifier into the ~~second~~ subset of code data to be transmitted. This is, in particular, the case if a learning or user-configurable remote control device is used and 10 ~~used~~ to control several electronic devices from different manufacturers. For each electronic device, the transmission protocol has to be identified and entered into the learning remote control device.

[0030] Once the message includes the code data, with or without 15 the identifier, this code data signal is transmitted (TCM) to the first electronic device.

[0031] The code data is transmitted burst-wise to the first electronic device either as a batch including all the code data to be transferred or as a series of successive signals. Once the code 20 data, with or without the identifier, are received by the first electronic unit, said data can be stored in the second memory 18. If the data input is used to receive the code data signal, the data input is preferably received from a signal decoder adapted to retrieve the subset and the identifier, if present, from the 25 received code data signal. The retrieved code data is then stored

in the second memory at successive addresses generated by an address generator of the first electronic device.

[0032] The first electronic device preferably includes a verification unit which is part of the data processing unit 24. The verification unit ~~is adapted to compare~~compares received code data with the code ~~date~~data stored in the second memory 18, in order to avoid that the same code data are stored twice. For this purpose, the verification unit is connected to the second memory 18 and to the interface 19, where the code data signal is input.

[0033] Upon receipt (RC, see Figure 6) of a code data signal by the interface 19, the verification unit reads (RD) the stored code data and compares (COM) the received code data with the code data stored in the second memory. If the received code data is already present or is not yet present in the second memory 18, the verification unit generates a second (2F) or a first (1F) flag, respectively. Under control of the first flag, the received code data is stored (S) in the second memory, whereas under control of the second flag, the received code data is ignored (OV) and access to the second memory is inhibited.

[0034] If the verification unit detects that the code data is already present, it may also verify whether the received code data is an updated version of the stored code data and, if this is the case, replace the stored code data with the updated code data. Thus, the contents of the second memory can be kept up-to-date. A

user who reloads ~~his~~ the first memory 16 in the remote control device 1, will then always have an updated contents.

[0035] The present invention provides not only a possibility to load or reload the first memory but, if the code data are available
5 from a common source, such as, a CATV provider or an Internet provider, also a possibility to complete or update the first memory of ~~his~~ the remote control device 1.

[0036] When the user now needs to update his/her remote control device 1 or to reload the first memory 16 of his/her remote control
10 device 1, for example, because the contents has been lost due to a battery failure, he/she can download the code data from the second memory. For this purpose, the user activates his/her remote control device 1 by pressing a call key associated with the first
15 electronic device 5. This causes a calling signal to be generated and transmitted to the first electronic device 5. Upon receipt of such a calling signal, the first electronic device 5 will start to address the second memory 18 ~~or to~~ download the code data from the second memory 18. Depending on the configuration of the remote control device 1, different code data will then be transmitted to
20 the remote control device 1, where they can be stored in the first memory 16. This is effected either by means of the transmitters/receivers 15 and 20 or the wired connection, if available.

ABSTRACT+ OF THE DISCLOSURE

In an arrangement including a remote control device and at least a first electronic device, ~~said the~~ remote control devices
5 ~~having includes~~ a first memory for storing a set of code data for controlling a further electronic device, ~~which the~~ first memory is being connected to an input of a signal generator to supply for supplying the ~~said~~ code data to ~~said the~~ input, ~~which the~~ signal generator ~~is adapted to generate~~ generating, on the basis of ~~said~~
10 the code data, control signals for controlling ~~said the~~ further electronic device, and ~~to transmit said~~ transmitting these control signals to ~~said the~~ further electronic device, ~~said~~. The first electronic device ~~having includes~~ a data input ~~arranged to receive for receiving~~ data from ~~said the~~ remote control device, and
15 ~~the said~~ remote control ~~has device includes~~ a code data output unit connected to ~~said the~~ first memory, ~~said~~. The code data output unit ~~having has~~ a further input for receiving an upload signal and ~~being adapted to read~~ reads, under control of ~~said the~~ upload signal, at least a subset of ~~said the~~ set of code data from ~~said the~~ first
20 memory, ~~said~~. The code data output unit ~~being further adapted to transmit said~~ transmits the subset of code data burst-wise to ~~said the~~ data input of ~~said the~~ first electronic device, ~~which and~~ first electronic device includes a second memory for storing a received subset of code data.

25

PHBE 000021

~~Fig. 1~~